

SERIES 61

SOLENOID VALVE 3/2 WAY N.O.

Elettrovalvola 3/2 vie N.A.

HIGHLIGHTS


- 3/2 way direct acting Normally Open (NO)
- 0 – 15 bar
- Serviceable Valve
- Seals/Tenuta: NBR – EPDM – FKM
- ED 100%
- Fixing points

PRODUCT DESCRIPTION

Solenoid valve 3/2 way, normally open. The body valve is made in brass as well as the core tube. The valve is serviceable in order to allow ordinary maintenance. Two fixing points on the body valve help the installation. Suitable for many different fluids. Very versatile valve, useful for many different applications.

DESCRIZIONE PRODOTTO

Elettrovalvola 3/2 vie, normalmente aperta. Il corpo valvola e cannotto centrale sono realizzati in ottone. La valvola è ispezionabile per consentire la manutenzione ordinaria. Due punti di fissaggio sul corpo aiutano l'installazione della valvola. Compatibile con molti fluidi diversi. Valvola molto versatile, utile per molte applicazioni differenti.



GENERAL FEATURES / CARATTERISTICHE GENERALI

Body material / Materiale corpo	Brass		
Seal material / Materiale di tenuta	EPDM	NBR	FKM
Temp. °C	140°	90°	150°
Tube material / Materiale tubo	Brass		
Working fluids / Applicazioni fluidi	Air, water, steam, Gas, Light Oil		
Electrical connect. / Connes. elettrica	6,3 x 0,8 fast-on terminal - UNI ISO 4400		
Insulation class / Classe di isolamento	H		
Coil voltage / Voltaggio	220-230VAC 50-60Hz	100-120VAC 60Hz	12-24 VDC
Coil power / Potenza bobina	17 VA	22 VA	16 W
Ambient temp. / Temp. ambiente	120°C	80°C	80°C
Fluid temp. / Temp. fluido	150°C	150°C	150°C
Approvals / Approvazioni	VDE; CE	UL	CE

SPECIFICATIONS / CARATTERISTICHE

CONNECTION		ORIFICE Ø (mm)	KV m³/h	M.O.P.D. (bar)		DIMENSIONS (mm)			CODE
in/out	3 [^] way*			AC	DC	A	B	C	
G 1/8	G 1/8	1.5	0.067	15	10	35	91	47	6111
G 1/8	G 1/8	2.0	0.122	10	7	35	91	47	6111
G 1/4	G 1/8	1.5	0.067	15	10	35	91	47	6112
G 1/4	G 1/8	2.0	0.122	10	7	35	91	47	6112
G 1/4	G 1/8	2.8	0.210	5	3	35	91	47	6112
Flange	G 1/8	1.5	0.067	15	10	33	74	47	6170
Flange	G 1/8	2.0	0.122	10	7	33	74	47	6170

* 3a way orifice Ø (mm): 1,5

HYDRAULIC CONNECTION

2/2 WAY NO		
IN/OUT G1/8"	IN/OUT G1/4"	FLANGE
6111	6112	6170

