

Cod. TEMP/AEC13



-TIMER PER REGOLAZIONE TEMPI D'INTERVENTO.

TEMPO: OFF 0,5÷45 minuti REGOLABILI
ON 0,5÷10 secondi REGOLABILI
VOLTAGGIO: 24V÷240V D.C., A.C. 50/60Hz \pm 10%
CONSUMO: 4mA MAX
TEMPERATURA: -40°C +60°C
PROTEZIONE: IP65 CON CONNETTORE TRIPOLARE UNI ISO 4400 (DIN43650 A)-IP65

-ADJUSTABLE TIMER TO PRESET DUTY CYCLE.

TIME: OFF 0,5÷45 minutes ADJUSTABLE
ON 0,5÷10 seconds ADJUSTABLE
VOLTAGES: 24V÷240V D.C., A.C. 50/60Hz \pm 10%
POWER CONSUMPTION: 4mA MAX
TEMPERATURE: -40°C +60°C
PROTECTION CLASS: IP65 WITH THREE POLE PLUG CONNECTOR UNI ISO 4400 (DIN43650 A)-IP65

-TIMER FUER REGELUNG DER SCHALTZEITEN.

SCHALTZEITEN: OFF 0,5÷45 Minuten EINSTELLBAR
ON 0,5÷10 Sekunden EINSTELLBAR
SPANNUNGEN: 24V÷240V D.C., A.C. 50/60Hz \pm 10%
STROMVERBRAUCH: 4mA MAX
TEMPERATUR: -40°C +60°C
ISOLATIONSKLASSE: IP65 MIT DREIPOLIGEM STECKER UNI ISO 4400 (DIN43650 A)-IP65

PESO/WEIGHT: 550 gr.